

Filter Trolley

Features & Benefits

Filter trolleys are critical to any pro-active, fluid management program and provide a number of benefits:

- *Guaranteed cleanliness of delivered & recirculated fluid.*
- *Secure transfer of fluids means the right fluid in the right location.*
- *Extends the life of oil and components when used proactively.*
- *Standardised process reduces spill risk and associated environmental concerns.*



Model
FT25-SV

Guaranteed performance in a cost effective package!

	FT20-LV	FT25-SV	FT25-HV
Flow	20 LPM	25 LPM	25 LPM
Fluid Range	< 150 cst	320 cst	> 320cst
Power	240V / 50Hz, with start/stop station & 3 metre power cable	240V / 50Hz, with start/stop station & 3 metre power cable	240V / 50Hz, with start/stop station & 3 metre power cable
Pump	Gear type	Gear type	Gear type
Filter	Pall SRT UR219 13" assembly	Pall SRT UR319 20" assembly	Pall SRT UR319 40" assembly
Suction / Delivery Hoses	¾" ID x 3 metres (suction hose fitted with drum spike)	1" ID x 5 metre	1" ID x 5 metre
Trolley	Heavy duty construction with inflatable tyres	Heavy duty construction, solid rubber tyres	Heavy duty construction, solid rubber tyres
Dimensions	H = 1300mm, W = 620mm & D = 500mm	H = 1300mm, W = 620mm & D = 500mm	H = 1400mm, W = 620mm & D = 500mm
Weight (dry)	55kg	60kg	65kg
Price			

Quality • Reliability • Knowledge