



TRUCK & FARM GREASE

ALMATEK[®]

LE 1233 NLGI #2

LE 1235 NLGI #1



- The Original Truck & Farm Grease proven to extend pin & bush life by a factor of 3x over competitor greases.
- The only Truck & Farm grease containing Quinplex[®] resulting in a grease that is waterproof whilst remaining pound out & impact resistant.
- Available in Summer & Winter formulations giving you greater flexibility in Australia's demanding and changing climates.





TRUCK & FARM GREASE

Technical Specifications

	<u>1233</u>	<u>1235</u>
Thickener Type	Lithium 12-Hydroxy	Lithium 12-Hydroxy
Texture	Stringy	Stringy
Color	Red	Red
NLGI Grade	2	1
Worked 60 Penetration ASTM D217	275	320
Dropping Point °C (°F), ASTM D2265	177 (350)	177 (350)
Base Fluid Characteristics		
Flash Point °C (°F) (COC), ASTM D92	204 (350)	204 (350)
Viscosity @ 100°C, cSt, ASTM D445 (without Quinplex)	11.7	11.7
Viscosity @ 40°C, cSt, ASTM D445 (without Quinplex)	144.0	144.0
Viscosity @ 40°C, cSt, ASTM D445 (with Quinplex)	2,200	2,200
Pour Point °C (°F), ASTM D97	-9 (15)	-9 (15)
Oxidation drop in psi @ 100 hrs, ASTM D942	5	5
Corrosion Prevention DI H2O, ASTM D1743	Pass	Pass
Water Spray-off % loss, ASTM D4049	6	13.85
Water Wash-out @ 37.8°C (100°F), % loss, ASTM D1264	10.4	4.82



Truck & Farm Grease is specifically designed for use in the agriculture and transport industries. It is a proven performer for heavy duty applications, including pins & bushes, bearings and chassis pivot points, where a high level of tackiness is desired to keep the lubricant in place.

ALMATEK® is a Lithium 12-Hydroxy based grease which also contains ALMASOL® Lubrication Engineer's exclusive "wear reducing" agent.

Available direct from
Lubrication Engineering Pty Ltd or visit
www.lubeng.com.au/distributors.html
 to find your nearest stockist

